

GT4260

Track-Mounted Stacking Conveyor



Main Conveyor

- 60' x 42" (18.3 x 1.1m)
- Variable-angle troughing rollers, 3-roll set x 4" (101.6mm) dia.
- 6" (152.4mm) disc return rollers
- 11" (279.4mm) self-cleaning tail pulley
- 13" (330.2mm) head pulley
- Primary spring-mounted face scraper

Chassis

- 18" (457.2mm) channel frame
- Bolted track frame design
- Pendant remote control (wireless optional)

Power and Hydraulics

- CAT® C4.4 136hp tier IV diesel engine
- 120 gal (454L) fuel tank
- 130 gal (492L) hydraulic oil reservoir
- Oil cooler
- Engine-mounted hydraulic pump to operate all machine functions.
- NEMA- 4 Rated instrument panel: Hour meter, emergency stops

Hopper/Feeder

- 13' x 48" (4 x 1.2m) belt feeder
- 8 cubic yard (6.1 cubic meter) capacity
- Hydraulic support legs
- Heavy-duty, 25-degree sloped grizzly with 6" (152mm) standard openings
- Hydraulic remote tipping grid with folding wing extensions

Options

- Wireless track remote
- 15' (4.6m) hopper feeder in lieu of 12' (3.7m) hopper feeder
- Heavy-duty grizzly section
- Shredder
- Vibrating grid
- Auxiliary circuit
- Full length rubber skirting
- Dust suppression
- Belt scale
- Immersion heater
- Block heater

Physical/Operating Characteristics

Dimension	Standard	Metric
Plant Capacity*	700 TPH	635 MTPH
Physical Operation Characteristics (Working 22°)		
Overall conveyor length	59' 6"	18.1m
Foot print length	73'	22.3m
Discharge height	29'	8.8m
Physical Transport Characteristics		
Transport length	42' 7"	12.9m
Transport height	11' 6"	3.5m
Transport width	9' 5"	2.9m
Weight	45,700lb	20,729kg

*Plant capacity will vary with conditions.



Astec Mobile Screens, Inc.
2704 West LeFevre Road
Sterling, IL 61081
1 (800) 545-2125
mail@kpijci.com
www.kpijci.com

NOTE: CONSULT FACTORY FOR EXACT DIMENSIONS, specifications are subject to change without notice.

Because Kolberg-Pioneer, Inc., Johnson Crushers International, Inc. and Astec Mobile Screens, Inc. may use in their catalog and literature, field photographs of their products which may have been modified by the owners, products furnished by Kolberg-Pioneer, Inc., Johnson Crushers International, Inc. and Astec Mobile Screens, Inc. may not necessarily be as illustrated therein. Also continuous design progress makes it necessary that specifications be subject to change without notice. All sales of the products of Kolberg-Pioneer, Inc., Johnson Crushers International, Inc. and Astec Mobile Screens, Inc. are subject to the provisions of their standard warranty. Kolberg-Pioneer, Inc., Johnson Crushers International, Inc. and Astec Mobile Screens, Inc. do not warrant or represent that their products meet any federal, state, or local statutes, codes, ordinances, rules, standards or other regulations, including OSHA and MSHA, covering safety, pollution, electrical wiring, etc. Compliance with these statutes and regulations is the responsibility of the user and will be dependent upon the area and the use to which the product is put by the user. In some photographs, guards may have been removed for illustrative purposes only. This equipment should not be operated without all guards attached in their normal position. Placement of guards and other safety equipment is often dependent upon the area and how the product is used. A safety study should be made by the user of the application, and, if required additional guards, warning signs and other safety devices should be installed by the user, wherever appropriate before operating the products.

Rev. 6/19